



PP Camlock Coupling Type DC

With years of experience in production PP Camlock Coupling Type DC, NingBo ZhenHai XunChi Hardware & Machine Co., Ltd. can supply a wide range of PP Camlock Coupling Type DC XunChi®. High quality PP Camlock Coupling Type DC can meet many applications, if you need, please get our online timely service about PP Camlock Coupling Type DC. In addition to the product list below, you can also customize your own unique PP Camlock Coupling Type DC according to your specific needs.

Product Description

Male Adapter With Female Thread

Product Name: PP Camlock Coupling Type DC XunChi®

Material: Polypropylene

Sizes: 1/2"-4"

MOQ: 50 PCS

Customizable contents: sizes, logo

Certificates: CE, ISO9001:2015

Competitive price

To learn more and get a quote, please leave your requirements on the form below.

Description:

Body materials: Polypropylene

Handle: stainless steel

Gaskets: Buna-N (NBR), EPDM

The thread of camlock fittings are BSP, BSPT, NPT

SIZE: 1/2" to 4"

Pressure :50-100 Psi(depending on size and temperature)

Operating temperature :-30-70°C (160°F)

When the temperature rises, the working pressure drops

Manufacture method: Injection molding

The use and connection way of cam and groove couplings: Type A camlock can usually be used with type D, type C, type B, type DC (Dust Cap) of the same size. To make a connection, simply slide the camlock adapter into the camlock coupling and with normal hand pressure, press the cam levers down.

Industry applications:

Industries: chemical, paint, agriculture, municipal, sewage

Applications: chemicals, solvents, varnishes, inks, fertilizers, wastewater